

## Explanation of Target Commands Used In Client build.xml file

Community Grids Lab, Indiana University

### **1.Introduction:**

This document provides a description of each of the commands used in the client build.xml file. There is no build.properties file associated with this file.

**compile:** Initiates compilation and echoes a message "Ready to run WSE Client targets".

Usage: \$ant compile

**release:** Echoes a message " WS-Eventing Release: Aug-2004 <http://www-128.ibm.com/developerworks/webservices/library/specification/ws-eventing/>" to the standard output

Usage: \$ant release

**clean:** Deletes the generated documents and classes folder

Usage: \$ant clean

### **2.Targets required to run source and sink client using AXIS**

**wseaxis-source:** Runs source service client endpoint

Usage: \$ant wseaxis-source

**wseaxis-sink:** Runs sink service client endpoint

Usage: \$ant wseaxis-sink

**wseaxis-sourceframe:** Runs source service client endpoint as a Frame

Usage: \$ant wseaxis-sourceframe

**wseaxis-sinkframe:** Runs sink service client endpoint as a frame

Usage: \$ant wseaxis-sinkframe

**wseaxis-sourceproxy:** Runs source proxy service client

Usage: \$ant wseaxis-sourceproxy

**wseaxis-sinkproxy:** Runs sink proxy service client

Usage: \$ant wseaxis-sinkproxy