

# **FIRMS-Explanation of Target Commands Used In Client build.xml file**

Community Grids Lab, Indiana University

## **1. Introduction**

This document provides a description of each of the commands used in the client build.xml file. There is no build.properties file associated with this file.

**Compile** = Initiates compilation and echoes a message "Ready to run FIRMS Client targets".  
Usage: \$ant compile

**Release** = Echoes a message "WS-ReliableMessaging Release: <http://msdn.microsoft.com/ws/2005/02/ws-reliablemessaging/> and WS-Reliability Release: Aug-2004 <http://docs.oasis-open.org/wsrn/2004/06/WS-Reliability-CD1.086.pdf> "to the standard output  
Usage: \$ant release

**Clean** = Deletes the generated documents and classes folder  
Usage: \$ant clean

## **2. Targets required running WSR source client using AXIS**

**run-sourceclient** = Runs source service client endpoint  
Usage: \$ant run-sourceclient

**run-sourceclientframe** = Runs source service client endpoint as a Frame  
Usage: \$ant run-sourceclientframe

**run-sourceproxyclient** = Runs source proxy service client  
Usage: \$ant run-sourceproxyclient

## **3. Targets required running WSRM source client using AXIS**

**run-sampleclient**: Runs source service client endpoint  
Usage: \$ant run-sampleclient